

## FLAXO SYNTHETIC ENAMEL

### Section 1: Company and Product Identification

Product Name:	Flaxo Synthetic Enamel
Product Code:	FP-0030
Product Type:	Oil Paint
Use of the substance/material	Oil-based Coating for interior metals & wood
Details of the supplier:	Flaxen Paints Industry L.L.C, Plot#593, New Industrial Area, Umm Al Quwain, United Arab Emirates Tel: +971 6 766 9442, Email: <a href="mailto:info@flaxenpaints.com">info@flaxenpaints.com</a>
Emergency Contact Detail:	Contact Person: Ajmal Khan Contact: +971-55-7530955

### Section 2: Hazards Identification

Skin irritation	Category 2
Eye irritation	Category 2
Skin Sensitization	Category 1
Aspirations Hazards	Category 1
Hazards to the aquatic environment chronic - category 2 flammable liquid 3	
Symbol	Inflammable eco hazards inhalation sign
Hazard Statement	Causes serious eye irritation, flammable liquid, vapor may be fatal swallowed and inhaled
<b>Precautionary Statements</b>	
General	P102 - Keep out of reach of children.
Prevention	P101 - Avoid release to the environment.
Response	P262 - Do not get in eyes, on skin, or on clothing. P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
Storage	Keep in a Dry & Cool Area.
Disposal	P501 - Dispose of contents and container in accordance with all local, regional, national or international regulations
Hazard(s) not otherwise specified:	None Known

# FLAXO SYNTHETIC ENAMEL

## Section 3: Composition / Information on Ingredients

Turpentine	CAS / ECP / 8006 - 64 - 2 (27 %)
<i>*There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.</i>	

## Section 4: First Aid Measures

Description of first aid measures	
General	In all cases of doubt, or if symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Eye contact	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse with fresh water for at least 15 minutes. Get medical attention if any discomfort continues.
Skin contact	After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.
Inhalation	Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Immediately rinse mouth with plenty of water. If person becomes uncomfortable or if ingested in large amounts. Take to hospital along with these instructions.
Indication of any immediate medical attention and special treatment needed	
Note to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatment	No specific treatment.
Protection to first-aider	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
See toxicological information (Section 11)	

# FLAXO SYNTHETIC ENAMEL




## Section 5: Fire Fighting Measures

Flash point	91F° (33° C) Explosion limit in Air (% by volume) n/a
<b>Extinguishing media</b>	
Suitable Extinguishing media	Recommended: alcohol-resistant foam, CO <sub>2</sub> , powders, water spray
Unsuitable Extinguishing media	Do not use water jet.
Hazards from the substance or mixture	Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
Hazardous decomposition or combustion products	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6: Accidental Release Measures

<b>Personal precautions, protective equipment and emergency procedures</b>	
For non-emergency personnel	Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
<b>Methods and materials for containment and cleaning up</b>	
Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop-up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain

## FLAXO SYNTHETIC ENAMEL

	and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in a container for disposal according to local regulations.
Reference to other sections	 See Section 1 for emergency contact information.  See Section 8 for information on appropriate personal protective equipment.  See Section 13 for additional waste treatment information.

### Section 7: Handling and Storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Storage temperature: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
Good industrial hygiene practice requires that exposure be maintained below the TLV (Threshold Limit Value) according to OSHA / PEL	

# FLAXO SYNTHETIC ENAMEL

## Section 8: Exposure Controls / Personal Protection

Control Parameter	
Occupational exposure limits	No exposure limit value known
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Exposure Controls	
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.
Eye/face protection	Use safety eyewear designed to protect against splash of liquids
Skin Protection	
Hand Protection	Use suitable protective gloves if risk of skin contact.
Body Protection	Personnel should wear antistatic clothing made of natural fibres or of high temperature-resistant synthetic fibres.
Other Skin Protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## FLAXO SYNTHETIC ENAMEL

Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
------------------------	--

### Section 9: Physical and Chemical Properties

<u>Information on basic physical and chemical properties</u>	
<b>Appearance:</b>	
Boiling Point	311° C (330° F) 115° (165° F)
Vapor Pressure	0.94 mm hg
Specific Vapor Density (Air = 1)	N/A
Solubility in water	N/A
Physical State	Liquid
Color	Different
Odor	Characteristics
Melting point	N/A
Evaporation rate	N/A
Flammability (solid, gas)	Flammable
Density	1.1 - 1.2
Solubility	Solvents
Partition coefficient: octanol/water	N/A
Auto-ignition temperature	N/A
Decomposition temperature	N/A
Viscosity	150 - 160 sec (sheen) A4 wp
<b>Other information</b>	
No additional information	

### Section 10: Stability and reactivity






Reactivity	No specific test data related to reactivity is available for this product or its ingredients.
Chemical stability	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	When exposed to high temperatures may produce hazardous decomposition products.

## FLAXO SYNTHETIC ENAMEL

Incompatible materials	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, and strong acids.
Incompatible materials to avoid	N/A
Hazardous decomposition products	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### Section 11: Toxicological Information

#### Information on toxicological effects

-  Acute effects associated with the use of the material eye irritation.
-  Exposure may result in Nausea, headache, and Confusion.
-  If Swallowed vapor is harmful.
-  He summated LD50 is > 5000 mg/kg.
-  This product is not suspected of human Carolingian NTP OV OHS.

### Section 12: Ecological Information

Toxicity	Toxic to aquatic life with long-lasting effects
----------	---

### Section 13: Disposal Consideration

Disposal methods	Do not allow into drains or watercourses. Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options
RCRA HAZARDS CLASS	








### Section 14: Transportation Information

	ADR/RID	ADN	IMDG	IATA
UN number	Not regulated	Not regulated	Not regulated	Not regulated
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-

## FLAXO SYNTHETIC ENAMEL

Environmental hazards	No	No	No	No
Special precautions for user	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. <b>UN NUMBER 1263 Paint-related materials Do not ship via Air without special packaging and labeling.</b>			
Transport in bulk according to IMO instruments	Not applicable.			

### Section 15: Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture	
Labeling	According to EEC directives for preparations
Symbol	Non Hazardous
Risk Phrase	 R 36/38-Irritating to eye & skin  R 43-May cause sensitization by skin contact.  R 51/53-Toxic to aquatic organisms
Safety Phrase	 S 7/9 Keep container tightly closed in well ventilated place.  S 28-after contact with skin, wash immediately with plenty of soap & water.  S 36/37/39-Wear suitable clothing's, gloves and eye/face protection.  S 61-Avoid release to the environment.

### Section 16: Other Information

**Issue date:** 1/06/2024

**Disclaimer:**

Flaxen Paints Industry LLC, cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Users should always consult Flaxen Paints for specific guidance on the general suitability of this product for their needs and specific application practices.